



Distance Is Safety®

The CBS ArcSafe® RRS-3-MB II remote racking system enables service personnel to remain outside the arc flash protection boundary while installing or removing the GE Magne-blast circuit breaker, significantly reducing the need for a full body arc flash hazard suit.

RRS-3 MB II

Key Features:

- Universal device operates 5kV M-26 and 15kV M-36 switchgear racking mechanisms
- Compatible with all elevating motor voltages and control circuit layouts
- Utilizes preexisting control circuit for raise and lower operations
- Breaker location feedback on control console
- No cubicle or switchgear modification necessary
- Ability to compare and quantify racking mechanism conditions using built in current monitor
- Optional radio remote allows for cordless operation from up to 100 ft
- Standard 30ft cable length on all cables (12 ft with radio remote option)
- Simple “plug and play” setup – no software programming required
- Optional tilt switch to alert operator of unsafe breaker tilt condition
- Powered using standard 120VAC wall power
- Simple pushbutton controls for install and remove operations
- Current control backup mode for cubicles with faulty control circuits

CBS ArcSafe Inc.
2616 Sirius Rd.
Denton, TX 76208

Tel: 940-382-4411
Fax: 940-382-9435

Website: www.CBSArcSafe.com
Email: info@CBSArcSafe.com

